



# LTS-60TH

**Designed with temperature & humidity sensors, monitoring assets conveniently!**

⚖ | 410g      ✂ | 105mm(L) × 64mm(W) × 46mm(H)  
 🌡 | -20° to 55° C      🔋 | rechargeable 12000mAh, 3.7V by Default

- 📍 Accurate location
- 📶 Dual Mode location
- 🔋 100 days standby time
- 🌡 Temperature and Humidity
- 🧲 Powerful magnet
- 🔄 Track playback
- 📞 Remote Monitoring
- 📱 SMS and APP
- 🕒 Can change interval time
- 💻 Tracking Platform
- ☁ Regular upload
- 🔄 Continuous operation mode
- 🔍 Query status
- 👤 Owner Binding

LTS-60TH temperature & humidity sensor is a multifunctional GPS locator suitable for cold chain vehicles. It is not only of moderate size and simple to install, but also integrates GPS/Beidou satellite positioning and GPRS communication technology. It has real-time positioning and tracking, Temperature and Humidity detection, alarm, and history data. Statistics, track playback, electronic fence and other functions.



## LTS-60TH

	Region	GNSS Type	Position Accuracy	Heart Beat
LTS-60TH	Worldwide	4G network: TDD LTE/ FDD LTE 3G network: WCDMA 2G network: GSM/ GPRS	5-10m	3 mins

Charging interface



SIM card



Powerful magnets



## SPECIFICATIONS

Working voltage	3.7 V , Built in rechargeable battery Optional 12000mAh/24000mAh
Cache storage	1000 pcs data
GPS Sensitivity	-161dBm
Sensor Accuracy	Humidity Sensor Accuracy $\pm 3$ %RH Temperature Sensor Accuracy $\pm 0.5$ °C Other accuracies and temperature ranges can be customized
Standby	Standby time 60-100 Days, Working time 20-30 Days,
Storage Temp	-40°C to +85°C
Working Temp	-20°C to +55°C
Bands	LTE FDD: B1/B2/B3/B4/B5/B7/B8/B28 LTE TDD: B40 LTE FDD: B1/B2/B3/B4/B5/B7/B8/B28LTE TDD: B40 WCDMA: B1/B2/B5/B8850/800/900/1900/2100MHz GSM:850 900 1800 1900
Waterproof	IP67 Waterproofing grade
Temperature line	1M (standard), MAX 20 meters
Powerful magnet	Extraposition